



Benefits:

- Robust construction
- High IP protection class
- High chemical resistance
- Vibration-proof mounting
- Camera mount included
- Nine separate windows prevent reflections of the LED lights into the lens
- Tested and approved by BASLER
- Good heat dissipation thanks to heat conductive tape between camera and enclosure
- Manufacturers glare shield not required



Technical Details:

Dimensions (w x h x l, without cable gland and dovetail profiles)	220 x 120 x 90mm
Weight (without dovetail profiles)	Approx. 1800g
Window Material	BK7, double sided ARC
Window Diameter	16.5mm
Window Seal	Hytrell
Colour	Light grey, RAL 7001 other colours on request
Enclosure Material	Powder Coated Aluminum
Enclosure Seals	Polyurethane
Options	- Dovetail profiles - Pressure equalising valve for outdoor use

Protection Class	IP66 (Nema 4) IP67 (Nema 6)
Cable Gland Aperture (max. connector size)	16.5mm
Cable Diameter	4-6.5mm
Cable Gland Seal	TPE



The mount guarantees good heat dissipation



Only a few components form the enclosure for the Basler Time-of-Flight camera

Accessories:

Product	Image	Order No.	Product	Image	Order No.
Mounting Kit 1		5.010.000	Mounting Kit 9		5.090.000
Mounting Kit 2		5.020.000	Mounting Kit 10		5.100.000
Mounting Kit 6		5.060.000	Mounting Kit 15		5.150.000
Mounting Kit 7		5.070.000	Mounting Kit 16		5.160.000
			Mounting Kit 17		5.170.000

Order Numbers:

Chameleon TOF	
Enclosure Type	Order Number
Without dovetail profiles	20.105.190
Including dovetail profiles	20.105.191



