



product introduction

The SX30-RMH Series of Prox Lights feature a single high current LED enclosed in a 30mm Barrel Style Housing. The SX30-RMH Series feature an NPN and PNP strobe signal with a 0-10 VDC analog intensity control signal for added versatility. The SX30-RHM Series has multiple mounting options allowing for ease of install and comes with two mounting nuts.



product features



- 30mm Barrel Style Housing
- M12 Quick Disconnect
- Driver built in – No External wiring to a driver
- PNP and NPN Strobe input
- Continuous operation or Strobe mode
- Analog intensity 0-10VDC signal
- Standard optics provide tight focused light



product specifications

Electrical Input	24 VDC +/- 5%
Current	Max. 250mA
Wattage	Max. 6W
Strobe Input	PNP ► +4VDC or greater to activate. NPN ► GND (<1VDC) to activate
PNP Line	3.7mA @ 3VDC 6.2mA @ 5VDC 12.6mA @ 10VDC 30.4mA @ 24 VDC
NPN Line	22mA @ Common (0VDC)
Red Indicator LED	LED Strobe Indicator ON = Light Active
Green Indicator LED	ON = Power
Continuous Mode	Light will be in continuous mode by leaving signal on strobe input active
Analog Intensity	The output is adjustable from 10 -100% of brightness by a 0 -10 VDC signal
Connection	5 pin M12 connector
Ambient Temperature	-20° - 50° C (-4° - 122° F)
Lifespan	100,000 hrs
IP Rating	IP65
Compliances	CE and RoHS
Weight	~99g
IEC 62471 Rating	See page 4



product number key

SX30-RMH – XXX – X* → Part Number Key

Product Family:
Prox Light
SX30-RMH

Color:
365, 395 – UV
470 – Blue
505 – Cyan
530 – Green
625 – Red
850, 940 – IR
WHI - White

Lenses:
W – Wide
L - Line

* Lights come standard with narrow lenses
CE and RoHS Compliant



warnings



Attention

Please note that the power requirements are 250mA at 24VDC. Failure to supply light with 250mA will result in non-repeatable lighting. Contact Smart Vision Lights for more information.



wiring configuration

If Analog 0-10 VDC is not used to control light intensity;
+VDC (24VDC) must be connected to Analog Input - Jumper pin 5 to pin 1

	Pin	Function	Signal	Wire Color
	1	Power In	+24VDC	BROWN
	2	NPN	Sinking Signal	WHITE
	3	GND	Ground	BLUE
	4	PNP	Sourcing Signal	BLACK
	5	Intensity Control	0-10VDC	GREY †

† Some cables use green with yellow stripe for 0-10V adjustment



mounting & accessories



Power Cables
5m, 10m, 15m



PB30-M1
Swivel Mount



PB30-M2
Slotted Block Mount



PB30-M3
Slotted Right Angle



PB30-M6
Bolt-on Block Mount




Diffuser Kits
Available




SX30-RMH-XXX

Working Distance mm (inches)	Pattern (80%-100% measured intensity)	
	mm (Inches)	
.5m (19.7")	80mm(~3") D	
1m (39.4")	185mm(~7") D	
Typical output performance		Illumination (Lux)
Distance = .5 meter		4200
<i>Illumination measurement taken on White Lights – 6500K</i>		




SX30-RMH -XXX-W


Working Distance mm (inches)	Pattern (80%-100% measured intensity)	
	mm (Inches)	
.5m (19.7")	205mm(~8") D	
1m (39.4")	415mm(~16") D	
Typical output performance		Illumination (Lux)
Distance = .5 meter		1300
<i>Illumination measurement taken on White Lights – 6500K</i>		



SX30-RMH -XXX-L

Working Distance mm (inches)	Pattern (80%-100% measured intensity)	
	mm (Inches)	
.5m (19.7")	255mm(~10") H x 115mm(~4.5") V	
1m (39.4")	460mm(~18") H x 250mm(~10") V	
Typical output performance		Illumination (Lux)
Distance = .5 meter		1900
<i>Illumination measurement taken on White Lights – 6500K</i>		





risk group

According to IEC 62471:2006. Full documentation upon request.

Notice

Exempt Group: No photo biological hazard to eyes or skin even for continuous, unrestricted use.
Applicable for wavelengths: 625, 850, and 940.

Caution

Risk Group 1: Possibly hazardous optical radiation emitted from this product. Do not stare at operating lamp. May be harmful to eye. Safe for most applications except prolonged exposures.
Applicable for wavelengths: 395, 470, 505, 530, and WHI.

Notice

Risk Group 1: UV emitted from this product. Minimize exposure to eyes and skin. Use appropriate shielding. Safe for most applications except prolonged exposures.
Applicable for wavelengths: 395

Caution

Risk Group 2: UV emitted from this product. Eye or skin irritation may result from exposure. Use appropriate shielding. Does not pose optical hazard if aversion responses limit exposure.
Applicable for wavelengths: 365