



For FA/Machine Vision
Fixed Focal

HF50HA-1B

Applicable camera (model)

1 2/3 1/2 1/3 1/4

FIXED
Fixed Focal

TELE
Telephoto Long Focal

1.5 Mega
For Megapixel Camera


MANUAL
Manual Iris

C-mt
C Mount

METAL
Metal Mount



- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Low-distortion design achieving accurate image input.
- Compact, lightweight and robust design, supporting various systems.
- Focus & iris lock tab provided, supporting environments such as vibration.



Focal Length (mm)		50
Iris Range		F2.3 ~ F22
Operation	Focus	Manual
	Iris	Manual
Angle Of View (H×V)	2/3"	10°03' × 7°33'
	1/2"	7°19' × 5°30'
	1/3"	5°30' × 4°07'
Focusing Range (From Front Of The Lens) (m)		∞ ~ 0.5
Object Dimensions at M.O.D. (H×V) (mm)	2/3"	77 × 57
	1/2"	56 × 42
	1/3"	42 × 31
Back Focal Distance (in air) (mm)		15.26
Exit Pupil Position (From Image Plane) (mm)		-25
Filter Thread (mm)		M25.5 × 0.5
Mount		C
Mass (g)		45

Remarks
 • With Metal Mount
 • With Locking Knob for Iris and Focus



For FA/Machine Vision
Fixed Focal

HF75HA-1B

Applicable camera (model)

1 2/3 1/2 1/3 1/4

FIXED
Fixed Focal

TELE
Telephoto Long Focal

1.5 Mega
For Megapixel Camera

MANUAL
Manual Iris


C-mt
C Mount

METAL
Metal Mount



- High-resolution design, providing support for up to 1.5 megapixel camera resolution.
- Low-distortion design achieving accurate image input.
- Compact, lightweight and robust design, supporting various systems.
- Focus & iris lock tab provided, supporting environments such as vibration.

*Photograph is a similar model.



Focal Length (mm)		75
Iris Range		F2.8 ~ F22
Operation	Focus	Manual
	Iris	Manual
Angle Of View (H×V)	2/3"	6°43' × 5°02'
	1/2"	4°53' × 3°40'
	1/3"	3°40' × 2°45'
Focusing Range (From Front Of The Lens) (m)		∞ ~ 1.1
Object Dimensions at M.O.D. (H×V) (mm)	2/3"	114 × 85
	1/2"	83 × 62
	1/3"	62 × 47
Back Focal Distance (in air) (mm)		15.74
Exit Pupil Position (From Image Plane) (mm)		-27
Filter Thread (mm)		M30.5 × 0.5
Mount		C
Mass (g)		55

Remarks
 • With Metal Mount
 • With Locking Knob for Iris and Focus

G-7

FUJINON CCTV LENS

WWW.STEMMER-IMAGING.COM · IMAGING IS OUR PASSION

GERMANY
AUSTRIA
Phone: +49 89 80902-0
info@stemmer-imaging.de

UNITED KINGDOM
IRELAND
Phone: +44 1252 780000
info@stemmer-imaging.co.uk

FRANCE
Phone: +33 1 45069560
info@stemmer-imaging.fr

SWITZERLAND
LIECHTENSTEIN
Phone: +41 55 415 90 90
info@stemmer-imaging.ch

THE NETHERLANDS
BELGIUM · LUXEMBOURG
Phone: +31 575 798888
info@stemmer-imaging.nl

STEMMER®
IMAGING