


## Features

- IP68 Standards
- Stainless Steel 316 Housing
- Meets FDA Compliancy
- Designed to operate in food applications
- Driver built in – No External wiring to a driver
- Continuous operation or Strobe mode
- Dimmable via built in potentiometer
- Analog intensity via 0-10VDC signal
- PNP and NPN Strobe input



Electrical Input	Voltage - 24 VDC +/- 10%    Maximum 10 Watts
Analog Intensity	The output is adjustable from 0-100% of brightness by a 0 -10 VDC signal
Dimmable	The output is manually adjustable from 0-100% of brightness by potentiometer
Continuous Mode	Light will be in continuous mode by leaving signal on strobe input
Strobe	PNP ► +5VDC or greater to activate.    NPN ► GND (<1VDC) to activate
Strobe Mode	The Light will operate in either continuous or strobe mode. In strobe mode, the output pulse width will track the pulse width of the strobe pulse.



1 = 24VDC  
2 = NPN STROBE  
3 = GND  
4 = PNP STROBE  
5 = 0-10VDC Analog

Standard M12 mating cable color code:

BROWN  
WHITE  
BLUE  
BLACK  
\*GRAY (GREEN/YELLOW)

\* 5 pin Standard M12 mating cable must be used: +VDC must be connected to pin 5 if Analog 0-10 VDC is not used.

## SW75 – XXX – X\* —» Part Number Key

Product Family:  
Spot Light  
75mm

Color:  
625 – Red  
470 – Blue  
505 – Cyan  
530 – Green  
IR 850nm  
IR 940nm

Lenses:  
W - Wide  
L - Line

\* Lights come standard with Narrow lenses